

This MIFARE Classic® EV1 13.65MHz Smartcard and PIN code reader has an elegant design with backlit keys. AY-W6350 is an advanced model with multiformat outputs for high compatibility with standard host access controllers. It has a local menu to program facility code as well as Card & PIN credential modes. This fully-potted model resists dust and moisture at level IP65.

GENERAL DESCRIPTION

The AY-W6350 is the latest addition to Rosslare's family of MIFARE Classic EV1 card readers. It can read MIFARE Classic EV1 card serial number (CSN) from all ISO 14443A-3 type cards.

AY-W6350 has locally programmable modes for a 1- to 8-digit PIN code, with a high-security option of "PIN plus card", as well as a 3-digit facility code. Even with the unit's strong features, this reader is user-friendly and easy to install with an additional level of security in the form of a password-protected menu.

This reader supports Wiegand 26/32/34/40-Bit or Clock & Data output protocols. It has a 6-wire shielded cable interface to the host controller for power, data, LED control input, and tamper status. Backlight offers a higher level of user accessibility. Free from sharp edges, it is ideal for installations where style and functionality are highly important.

MAIN FEATURES

- Incorporates the ISO-14443A (MIFARE Classic EV1) ID Format Protocol
- Read range of up to 70 mm (2.8 in.)
- Backlit 3x4 keypad
- 8 programmable Proximity Card transmission formats, Wiegand 26- to 40-Bit or Clock & Data

- Smooth, attractive, and elegant industrial design
- Selectable LED control or buzzer control functions
- Made from tough polycarbonate plastic for improved performance in all weather conditions

PROFESSIONAL GRADE FEATURES

- Optical tamper sensor for cover and wall tamper detection
- 8 programmable PIN transmission formats for data and credential entry options
- Card + PIN mode for higher security
- Door bell key feature (from "*" key when interfaced with Rosslare controllers)
- Weather-resistant with epoxy potting (IP65)
- One tri-colored LED and integral sounder for programming and operation
- Programmable facility code
- Installation kit includes template label, security screw, and tool
- 60 cm (23.6 in.) 6-wire interface cable



SPECIFICATIONS

ELECTRICAL SPECIFICATIONS

Operating Voltage Range	5–16 VDC, from a linear type Power Supply (18 VDC is absolute maximum)
Input Current	Standby: 180 mA @ 12 VDC Maximum: 235 mA @ 12 VDC
■ Tamper Output	Open collector, active low, maximum sink current is 32 mA
OPERATIONAL SPECIFICATIONS	
LED Control Input	N.O., Dry Contact
Keypad	3x4 red backlit keys for PIN codes entry and local programming door bell key ('*') function (with Rosslare controllers only)
■ Built-In Reader	Maximum read range: 70 mm (2.8 in.) Operating frequency: 13.56 MHz Compatible Cards: MIFARE Classic® EV1 Compatible ISO-14443A
PIN Code Formats	8 selectable formats, from single to 8-digit PIN codes
Card Output Formats	8 selectable formats: Wiegand 26-Bit with Facility code, 32-Bit, 32-Bit Reversed, 34-Bit, 40-Bit, Clock & Data and Wiegand Card + PIN
Facility Code	Programmable
Indications and Sounds	Tri-colored light bar, built-in sounder with selectable LED/sounder control input
ENVIRONMENTAL SPECIFICATIONS	
Operating Environment	Indoor and outdoor use (all weather) – meets IP65
Operating Temperature Range	-31°C to 63°C (-25°F to 145°F)
Operating Humidity Range	0 to 95%
RFI Protection	> 20 V/m up to 1000 MHz
PHYSICAL SPECIFICATIONS	
Dimensions (H x W x D)	125 x 83 x 29.5 mm (4.9 x 3.3 x 1.2 in.)
■ Weight	230 g (8.1 oz)
SYSTEM COMPONENTS	The AY-W6350 is compatible with a variety of Rosslare's controllers as well as with many third-party systems.
PRODUCT WARRANTY	5-Year Limited Product Warranty

ABOUT ROSSLARE SECURITY

Rosslare Security Products manufactures and markets high-quality security products via its worldwide offices and channel partners. Since 1980, Rosslare has offered high-quality systems for enterprise, small business, and residential applications. With Rosslare, you receive the best of all worlds: world-class product engineering and design; professional customer service spanning the globe; and the quality and affordability of a vertically integrated and self-owned manufacturing facility. Our expansive product range features much more than access control solutions and guard patrol management systems; we also offer applications software – such as License Plate Recognition, Time & Attendance, and DVR/alarm integration.

www.rosslaresecurity.com

 $\mathsf{MIFARE}^{\circledast} \text{ is a trademark of NXP Semiconductors}$









